



Easy Network, Trustable

300Mbps Wireless N High Power Outdoor AP Router

WF2322



Features:

- > Comply with 802.11b/g/n standard, data rate up to 300Mbps
- > Maximum 1000mW Transmit Power enabling long range connectivity
- > Internal High gain 10dBi directional antenna, dual-polarity
- > IP55 Waterproof for case
- > Various WAN connection types- DHCP, PPPoE, Static IP, Russia PPPoE, Unifi PPPoE, L2TP/Russia L2TP, PPTP/Russia PPTP, WISP
- > Multiple wireless modes- AP, Router, WISP, AP + Client, AP + Repeater, WISP + Client, WISP + Repeater
- > ESD protection up to 15KV
- > Remote reset from power adapter

What it does:

The netis 300Mbps Wireless N High Power Outdoor AP Router WF2322 provides long range, high performance wireless Internet access over long distance. The maximum 1000mW transmit power enables you long range connectivity. Also, with 15kV ESD protection and IP55 Waterproof for case, WF2322 is suitable for harsh environment, providing users a stable and smooth networks connection.

www.netis-systems.com

300Mbps Wireless N High Power Outdoor AP Router

WF2322

Specification:

Wireless	
Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Signal Rate	Up to 300Mbps
Frequency Range	2.4-2.4835GHz
Transmit Power	<20dBm (For countries using CE Standards) <30dBm (For countries using FCC Standards)
Receive Sensitivity	-99dBm(Maximum)
Data Transfer Rate	802.11n: 40MHz(300Mbps, 270Mbps, 240Mbps, 180Mbps, 120Mbps, 90Mbps, 60Mbps, 30Mbps) 20MHz (144Mbps, 130Mbps, 115Mbps, 86Mbps, 57Mbps, 43Mbps, 28Mbps, 14Mbps) 802.11g:(54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 9Mbps, 6Mbps) 802.11b:(11Mbps, 5.5Mbps, 2Mbps, 1Mbps)
Wireless Mode	AP, Router, WISP, AP + Client, AP + Repeater, WISP + Client, WISP+ Repeater
Wireless Security	64/128-bit WEP WPA-PSK/WPA2-PSK (TKIP/AES) SSID Broadcast Enable/Disable/Wireless MAC Filtering
Hardware	
Standard	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX
Interfaces	2*10/100Mbps LAN Port
LED Indicator	Power, WLAN, LAN-Main, LAN-Secondary, Wireless Signal 1-4
Buttons	Reset
Antennas	1*10dBi directional Antenna, Dual-polarity
Power Supply	Proprietary PoE, DC 24V/0.5A
Software	
WAN Type	DHCP, PPPoE, Static IP, Russia PPPoE, Unifi PPPoE, L2TP/Russia L2TP, PPTP/Russia PPTP, WISP
Port Forwarding	Virtual Servers, UPnP, DMZ
QoS	Bandwidth Control
Access Control	MAC Filtering
Others	Dynamic DNS, PSE
Others	
Certification	FCC, CE
Environment	Operation Temperature: -30°C~70°C (estimated) Storage Temperature: -30°C~80°C (estimated) Humidity: 0~90% non-condensing ESD conductive: 15kV ESD Air: 10kV
Package	1* WF2322 1* 12V/500mA Power Adapter 1*PoE Injector 1* AC Power Cord 2* Cable Ties 1* Quick Installation Guide

Typical Applications



Application 1: Wireless Bridge



Application 2: WISP Connection



Application 3: Multiple Bridge



Application 4: Wireless Gateway

